## **Since 1969**



Technological, Economical, Ecological Differencies

## **2023 LAUNDRY MACHINES**

Distributor:



## **GATEWAY VENTURES FZE**

P6-71, SAIF Zone, Sharjah, United Arab Emirates Tel: +971 6 5573850 | Fax: +971 6 5573851 Website:www.gvhts.com | info@gvhts.com





# Technological, Ecological, Economical Differencies,







# Rising Stars...












## INDEX

Company Profile	6
Tolkar Future Full Automatic Loading Unloading Systems	8
Tolkar Carina Pass Through Tumble Dryers	10
Full Automatic Washer Extractors	11
Hygienic Barrier Type Washer Extractors	27
Tumble Dryers	30
Stacked Washer Extractors and Dryers Stacked Dryers	34
Speed Queen Stacked Washer Extractors / Tumble Dryers	35
Flatwork Ironers	36
Chest Heated Ironers	40
Linen and Towel Folding Machines	46
Feeders / Towel Rollers	50
Laundry Auxiliary Equipments	51
Colmac Automatic Tunnel Ironing Systems	53
Distributorships	54
Countries We Are Exporting To	55

# WASHING TECHNOLOGY

% MEASURABLE SUSTAINABLE ECONOMICAL & GREEN









### **COMPANY PROFILE**

TOLKAR has established in 1969 as a family business regarding to produce textile processing and commercial laundry machines in city of Izmir, TURKEY. From the very first date, continuous development, better quality and customer satisfaction have made up a principle by TOLKAR where at the present day constitutes from 3 splendid innovative production factories in İZMİR Ataturk Industrial Zone, distributorship of the leader manufacturers of their sectors for supplementary products. TOLKAR has its own reputation in the world by reaching the production capacity of 3500 machines per year of various models and exports more than 91 countries abroad. Besides, 18 Regional Branches with their Sales & Service Managements in Turkey TOLKAR has more than 30 distributors with their Sales & Service Managements in abroad, ensures the fastest sales and after sales servicing facilities to their customers.

Along the stage of development, TOLKAR is devoted itself to differ as technological, ecological and economical supremacies. Utilization of latest technologies and techniques in production, TOLKAR performs from starting up the design phase, consequent research & development, prototype production, factory tests, field tests and mass production by accomplishing the mentioned triple mission. All revolutionary inventions those differs as technological, ecological and economical supremacies; have been protected with their Patents in all over the world. All our innovations offer to our customers uncompromisable and inapproachable savings where at the same time minimize the effluent in order to protect the environment for a clean world to the next generations.

TOLKAR provides all capacities of commercial & industrial laundry machines along with auxiliary equipment including turnkey projects and all textile/garment processing, washing, dyeing machines, unique waterless technologies right alongside the distributorship of the leader brands such as BIKO, COLMAC, SPEED QUEEN and RENZACCI. In 2008, after acquisition of SMARTEX and its patented "Smart Balancing System", TOLKAR becomes the unique company who has the capability of manufacturing very high speed washer extractors by exerting 400 G force while spinning. Yet as the first and the only producer of the unique innovation introduced PolyRib ECO Drum, TOLKAR is proud to offer SMARTEX Miracle series which saves dramatically 50 % from the water, chemicals and heating energy and waste water along with the very first manufacturer of 'Direct Gas Heated' Washer Extractors.

Starting from 2013, TOLKAR announces to work on waterless and chemical free washing and processing technics by concentrating to develop Ozone Washing and Smart Flow Nano Bubble technologies for textile and garment industry in order to achieve dramatic reduction of water as well as to stop heavy chemical wastes. Today dissolution of the ozone gas within the water has achieved by TOLKAR wherein many garment processing steps can be done without chemicals and without any water discharge in shorter times. Same as Smart Flow Nano Bubble Spraying Technology achieves some steps without any water usage and without any discharge to environment.


In 2019, TOLKAR established the unmanned laundry and textile washing facilities with TOLKAR Future within the framework of Automation and Industry 4.0 applications. It has managed to establish an almost unmanned business by controlling all washing, drying, chemical transfer, recipe preparation and reporting from a single center by providing loading/unloading and textile transfers with automatic conveyors and shuttles.

With the consciousness of change alone is unchanging, TOLKAR will perpetuate the leadership in accordance with its mission to next generations.









1000 - 1500 KG/HOUR PRODUCTION WITH FULL AUTOMATION SYSTEM

ZERO REJECTION WITH MAXIMUM CLEANING PERFORMANCE SUITABLE FOR FLEXIBLE WORKING WITH STAND BY SYSTEM MAXIMUM PRODUCTIVITY WITH RAPID LOADING & UNLOADING





TOLKAR FUTURE Automatic Loading Unloading System

AUTOMATIC LOADING UNLOADING CONVEYOR & SHUTTLE SYSTEM ELIMINATES THE NEED FOR LABOUR 90%

CONTROLLED FROM CENTRALIZED COMPUTER INCLUDING RECIPE TRANSFER FULLY MAN FREE OPERATION ELIMINATES THE RISKS OF FAILURE AND MISTAKES MINIMUM CHEMICAL CONSUMPTION WITH AUTOMATIC CHEMICAL DOSING ACCOMPLISHED TRANSPORTATION CONVEYOR BEHIND THE DRYERSÍ FOR EASY TRANSPORT TO FINISHING (OPTIONAL)





TOLKAR Pass Through Tumbl		NA PT				
150 - 250 Kg						
		3000	5000			
Heating Type		Steam / Gas	Steam / Gas			
Capacity	(Kg)	150	250			
Drum Volume	(lt)	3.014	5.070		Humidity	
Drum Diameter	(mm)	1.600	1.980	Steam & Cas	control	
Drum Depth	(mm)	1.500	1.650	Steam & Gas heated	Infrared	PLC
Motor Power	(Kw)	5.5	5.5	models	control	controlled
Fan Motor Power	(Kw)	11	11		drying	touch screen
Steam Consumption	(Kg/Hour)	350	500		(Optional)	panel
Gas Heat Power	(Kcal)	99.000	173.250			
Air flow	(m <sup>3</sup> /Hour)	11.000	22.000	Front side	Compatible	ľ í
Width	(mm)	2.200	2.543	loading and	with automatic	Faster drying
Depth	(mm)	2.200	3.079	back	loading	time within
Height	(mm)	4.000	4.446	side unloading	unloading	20-25 min/cycle
Weight	(Kg)	3.000	4.9910	automotically	systems	
Tolkar reserves cha						

Tolka machines due to technological necessities without prior notice







#### SMARTEX MIRACLE Full Automatic Washer Extractors

225 - 340 Kg

				Miracle 2250	Miracle 3430
	*	Heating Type		Steam / Gas	Steam
		Loading Capacity	(Kg/Batch)	225	340
		Drum Volume	(lt)	2.280	3.398
Tank System		Motor Power	(Kw)	30	18,5
WATER RECOVERY		Gas Heat Power	(Kcal/hour)	132.000	-
Technology		Width	(mm)	1.915 (2.580)	2.175
		Depth	(mm)	2.770	2.550
60%	BACKWARDS TILTI	·····g···	(mm)	2.562	2.730
	EASY LOADING & UNLOAD	DING Tilted Height	(mm)	2.845	3.110
WATER SAVING		Weight	(Kg)	4.530	6.670
WATER CONSUMPTION Towel 1:1-1:2 L/R Linen 1:1-1:1,5 L/R Polyster 1:1 L/R	POLYRIB ECODRUM SYSTEM less water chemicals heating energy	POLYRIB DRUM 45% Longer textiles life	EXTR/ FO TOT VIBR	<b>OG</b> ACTION RCE ALLY ATION REE	




















400G EXTRACTION FORCE

> TOTALLY VIBRATION FREE

## TOLKAR ULTIMATE CONTROL SYSTEM

- USB programme transfer
- 20 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)



PLC Controlled 7" Touch Screen Panel

10" Touch Screen Panel for 225&340 models



#### Automatic Liquid Detergent Dosing

System in built dosing pumps for liquid detergent dosing. Integrated with reporting and weight scale systems (Wet Clean) - (Optional)













		Miracle 600	Miracle 1200
Heating Type		Elc/Stm/Gas	Steam / Gas
Loading Capacity	(Kg/Batch)	60	120
Drum Volume	(lt)	550	1.125
Motor Power	(Kw)	7,5	18,5
Gas Heat Power	(Kcal/hour)	33.000	66.000
Electric Heating Power	(Kw)	40	-
Width	(mm)	1.260	1.530
Depth	(mm)	1.890	2.415
Height	(mm)	1.765	2.030
Tilted Height	(mm)	-	2.370
Weight	(Kg)	1.290	2.230

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice



SMARTEX 1350





591ABTE 1500

		11	
		N. MA	-
		Miracle 1350	Miracle 1500
Heating Type		Steam / Gas	Steam / Gas
Loading Capacity	(Kg/Batch)	135	150
Drum Volume	(lt)	1.300	1.480
Motor Power	(Kw)	18,5	22
Gas Heat Power	(Kcal/hour)	66.000	66.000
Width	(mm)	1.585	1.750
Depth	(mm)	2.448	2.480
Height	(mm)	2.056	2.120
Tilted Height	(mm)	2.456	2.461
Weight	(Kg)	2.700	2.980

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice







#### SMARTEX MIRACLE Full Automatic Washer Extractors



		Miracle 2250	Miracle 3430
Heating Type		Steam / Gas	Steam
Loading Capacity	(Kg/Batch)	225	340
Drum Volume	(lt)	2.280	3.398
Motor Power	(Kw)	30	18,5
Gas Heat Power	(Kcal/hour)	132.000	-
Width	(mm)	1.915 (2.580)	2.175
Depth	(mm)	2.770	2.550
Height	(mm)	2.562	2.730
Tilted Height	(mm)	2.845	3.110
Weight	(Kg)	4.530	6.670

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

### DUST MATS & MOPS


- Sand separator
- Cyclone filter, self cleanable
- Laser check for tracing
- the mats
- Compatible with auto loading / unloading systems







#### SMARTEX MIRACLE+TS Full Automatic Washer Extractors



Water recovery tank

		Miracle 600	Miracle 1200	Miracle 1350	Miracle 1500	Miracle 2250
Heating Type		Elc/Stm/Gas	Steam/Gas	Steam/Gas	Steam/Gas	Steam/Gas
Loading Capacity	(Kg/Batch)	60	120	135	150	225
Drum Volume	(lt)	550	1.125	1.300	1.480	2.280
Recovery Tank	(lt)	180	360	400	450	700
Motor Power	(Kw)	7,5	18,5	18,5	22	30
Gas Heat Power	(Kcal/hour)	33.000	66.000	66.000	66.000	132.000
Electric Heating Power	(Kw)	40	-	-	-	-
Width	(mm)	1.260	1.530	1.585	1.750	1.915 (2.580)
Depth	(mm)	1.890	2.415	2.448	2.480	2.770
Height	(mm)	1.765	2.030	2.056	2.120	2.562
Tilted Height	(mm)	-	2.370	2.456	2.461	2.845
Weight	(Kg)	1.290	2.230	2.700	2.980	4.530

Tank System WATER RECOVERY Technology

> 60% water saving

> > Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

SMARTEX





## HYDRA Mini Midi Maxi Full Automatic Washer Extractors







360 G **EXTRACTION** FORCE

## 100% **HEAVY INDUSTRIAL CONSTRUCTION**

- ST37 balance weight system
- Engineered front & rear plates and drum construction
- Enhanced new belt-pulley system
- and bearing housing
- Unwelded inner drum

POWERSPRAY (Optional)







TELKAR







- USB programme transfer
- 20 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

FULLY STAINLESS STEEL

inner & outer drums, front, sides and top covers



PLC Controlled 7" Touch Screen Panel



Automatic Liquid Detergent Dosing System

System in built dosing pumps for liquid detergent dosing. Integrated with reporting and weight scale systems (Wet Clean) - (Optional)







#### 10 - 12 - 20 - 25 - 30 Kg



		Hydra Mini 10	Hydra Mini 12	Hydra Mini 20	Hydra Mini 25	Hydra Mini 30
Loading Capacity	(Kg/Batch)	10	12	20	25	30
Drum Volume	(lt)	100	120	208	254	300
Motor Power	(Kw)	1.5	2.2	3	4	4
Heating Power	(Kw)	6	8	9	12	15
Width	(mm)	825	825	990	990	990
Depth	(mm)	860	970	1.030	1.155	1.300
Height	(mm)	1.300	1.300	1.450	1.450	1.450
Weight	(Kg)	350	390	595	700	700

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





HYDRA Midi Full Automatic Washer Extractors

40 - 50 Kg



		Hydra Midi 40	Hydra Midi 50
Loading Capacity	(Kg/Batch)	40	50
Drum Volume	(lt)	400	500
Motor Power	(Kw)	5.5	7.5
Heating Power	(Kw)	18	24
Width	(mm)	1.180	1.180
Depth	(mm)	1.345	1.525
Height	(mm)	1.780	1.780
Weight	(Kg)	1.125	1.230

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





#### HYDRA Maxi Full Automatic Washer Extractors

60 Kg



		Hydra Maxi 60
		Steam/Elc.
Loading Capacity	(Kg/Batch)	60
Drum Volume	(lt)	586
Motor Power	(Kw)	7,5
Heating Power	(Kw)	36
Width	(mm)	1.700
Depth	(mm)	1.560
Height	(mm)	1.920
Weight	(Kg)	1.900

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice Wider Loading Door

Faster Heating with Enhanced Steam Inlet (3/4î)

Faster Water Intake with Enhanced Water Inlet (1î)

Double Drain System (2î)

**360 G** EXTRACTION FORCE







60 Kg





#### TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking
- USB programme transfer
- 20 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

Fully Stainless Steel Inner & Outer Drum

PLC

Controlled

7" Touch

Screen Panel

New Generation Enhanced Main Shaft and Sealing Fully Stainless Steel Covers

New Generation Heavy Industrial Construction New Generation Enhanced Drive System and Bearing Housing





HYDRA Maxi Full Automatic Washer Extractors

Hyd	lr	a	
Maxi	1	1	0

		Steam
Loading Capacity	(Kg/Batch)	110
Drum Volume	(lt)	1.100
Motor Power	(Kw)	15
Heating Power	(Kw)	60
Width	(mm)	1.875
Depth	(mm)	2.055
Height	(mm)	2.060
Tilted Height	(mm)	2.265
Weight	(Kg)	4.300

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice Wider Loading Door

Faster Heating with Enhanced Steam Inlet (1î)

Faster Water Intake with Enhanced Water Inlet (2î)

Double Drain System (4î)



TELKAR

360 G EXTRACTION FORCE







#### TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking
- USB programme transfer
- 20 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

Fully Stainless Steel Inner & Outer Drum



New Generation Enhanced Main Shaft and Sealing Fully Stainless Steel Covers

New Generation Heavy Industrial Construction New Generation Enhanced Drive System and Bearing Housing







TOLKAR MIRACLE Full Automatic Washer Extractors

#### 50 - 60 Kg



		Miracle 50	Miracle 60
Heating Type		Elc/Stm/Gas	Elc/Stm/Gas
Loading Capacity	(Kg/Batch)	50	60
Drum Volume	(lt)	500	600
Motor Power	(Kw)	7,5	11
Gas Heat Power	(Kcal/hour)	33.000	33.000
Electric Heating Power	(Kw)	24	36
Width	(mm)	1.610	1.850
Depth	(mm)	1.525	1.590
Height	(mm)	1.780	2.130
Weight	(Kg)	1.350	2.600

\* All specifications and features of Hydra Series will come along with Tolkar Miracle as standard.

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice



Inner & Outer Drums and Covers



Polyesters 1:1

L/R

and heating energy







7" Touch

Screen Panel

## **100% HEAVY INDUSTRIAL** CONSTRUCTION

#### **TOLKAR ULTIMATE CONTROL SYSTEM**

ŝ Remote access, instant mobile tracking

- USB programme transfer
- ۲ 20 ready recipes, 100 recipes
- Reporting, amount of laundry, consumption values and (i) working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

FORCE

		Norma Hygiene 20	Norma Hygiene 40	Norma Hygiene 60	Norma Hygiene 90	Norma Hygiene 120
Loading Capacity	(Kg/Batch)	20	40	60	90	120
Drum Volume	(lt)	200	400	600	900	1200
Motor Power	(Kw)	3	5,5	11	15	22
Heating Power	(Kw)	9	18	36	45	45
Width	(mm)	1.439	1.540	2.005	1.921	2.360
Depth	(mm)	967	1.161	1.450	1.382	1.450
Height	(mm)	1.590	1.737	1.996	2.171	2.060
Weight	(Kg)	785	1.190	1.600	2.200	2.750

\* All specifications and features of Miracle Series will come along with SMARTEX MIRACLE HYGIENE as standard.

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





# SMARTEX MIRACLE HYGIENE Hygienic Barrier Type Washer Extractors

60 Kg





		Miracle Hygiene 600	Miracle Hygiene1350	Miracle Hygiene2250
Heating Type		Electric/Steam	Steam/Gas	Steam/Gas
Loading Capacity	(Kg/Batch)	60	135	225
Drum Volume	(lt)	600	1.300	2.280
Motor Power	(Kw)	7,5	18,5	30
Electric Heat Power	(Kcal/hour)	40	-	-
Gas Heat Power	(Kcal/hour)	-	66.000	132.000
Width	(mm)	1.260	1.882	2.355
Depth	(mm)	1.890	2.475	2.770
Height	(mm)	1.765	2.206	2.522
Tilted Height	(mm)	-	2.456	2.692
Weight	(kg)	1.290	2.700	4.650

\* All specifications and features of Miracle Series will come along with SMARTEX MIRACLE HYGIENE as standard.

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice





# TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking ŝ,
- USB programme transfer •
- ۲ 20 ready recipes, 100 recipes
- **Reporting,** amount of laundry, consumption values and working hours are being reported. (Optional) (i)
- Smarteye centralized control and data acquisition (Optional) ۲






#### SMARTEX MIRACLE HYGIENE Hygienic Barrier Type Washer Extractors

135 - 225 Kg






10 X





CARINA Tumble Dryer Machines











GAS + STEAM HEATING SYSTEM (Optional for Models 4069 - 5070)

T. LKAR

FULLY STAINLESS STEEL OUTER CABINET (Optional)

#### TOLKAR ULTIMATE CONTROL SYSTEM

Remote access, instant mobile tracking

- USB programme transfer
- 10 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

k

PLC Contrelled 7" Touch Screen Panel FORWARD TILTING FOR EASY UNLOADING BACKWARDS TILTING FOR EASY LOADING - STANDART (Models 2200-4069-5070) (Optional for Model 1500)









		Carina 201	Carina 305	Carina 405	Carina 500	Carina 605	Carina 805	Carina 1000
Heating Type		Electric	Elc./Stm./Gas	Elc./Stm./Gas	Elc./Stm./Gas	Elc./Stm./Gas	Elc./Gas	Elc./Stm./Gas
Capacity 1/20-1/15	(kg)	10/14	15/20	20/27	25/33	30/40	40/53	50/66
Drum Volume	(lt)	201	305	405	500	605	800	1.000
Drum Motor Power	(Kw)	0,37	0,75	0,75	0,75	0,75	1,1	1,1
Fan Motor Power	(Kw)	0,75	0,75	0,75	0,75	0,75/1,5/0,75	1,5	2,2/3/2,2
Electric Heating Power	(Kw)	12	14	14	24,5	21	42	63
Steam Consumption	(Kg/hour)	-	38	38	38	44	-	81
Gas Heat Power	(Kcal/hour)	-	18.000	23.000	23.000	25.000	39.600	39.600
Air flow	(m³/hour)	1.300	1.300	1.300	1.300	1.500	3.900	3.900/4.500/4.500
Width	(mm)	825	970	970	970	1.040	1.040	1.355/1.420/1.360
Depth	(mm)	915	870	1.020/1.100	1.180/1.240/1.240	1.215	1.650	1.500
Height	(mm)	955	1.650/1.780/1.790	1.650/1.780/1.790	1.650/1.780/1.790	1.780/1.860/1.910	1.860	2.130/2.250/2.380
Weight	(kg)	140	280	285	325	365	450	700

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice









2200 - 2700 - 4069 - 5070

		Carina 1200	Carina 1500	Carina 1500*	Carina 2200	Carina 2700	Carina 4069	Carina 5070
Heating Type		Elc./Stm./Gas	Elc./Stm./Gas	Elc./Stm./Gas	Steam/Gas	Steam/Gas	Steam/Gas	Steam/Gas
Capacity 1/20-1/15	(kg)	60/80	75/100	75/100	110/145	135/180	200/270	250/340
Drum Volume	(lt)	1.200	1.500	1.500	2.200	2.700	4.069	5.070
Drum Motor Power	(Kw)	1,5	1,5	1,5	3	3	5,5	5,5
Fan Motor Power	(Kw)	1,5/2,2	2,2/3/3	3/3	4x1,1/2x3	4x1,1/2x3	4x3/2x3	4x3/2x3
Electric Heating Power	(Kw)	63	63	63	-	-	-	-
Steam Consumption	(Kg/hour)	95	110	110	160	270	400	500
Gas Heat Power	(Kcal/hour)	49.500	57.000	57.000	99.000	99.000	148.500	173.250
Air flow	(m³/hour)	4.500/6.400/6.400	4.500/6.400/6.400	6.400/6.400	6.400/6.400	11.000	22.000/11.000	22.000/11.000
Width	(mm)	1.355/1.420/1.360	1.355/1.420/1.360	1.800/1.800	2.120/2.000	2.104/2.043	2.240/2.290	2.474/2.489
Depth	(mm)	1.700	2.040	2.240	2.293/2.300	2.415/2.411	2.649/2.704	2.780/2.780
Height	(mm)	2.130/2.250/2.380	2.130/2.250/2.380	2.330/2.650	2.671/2.315	2.742/3.203	3.105/3.321	3.224/3.629
Tilted Height	(mm)		-	2.550/2.650	2.698/3.300	2.808/3.328	3.390/3.699	3.484/3.902
Weight	(kg)	725	900	1.100	1.500	2.300	3.280	3.910

\* with forward tilting option. Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice







1 11 1



360 G **EXTRACTION** FORCE

**DIRECT GEAR BOX DRIVE** DRYER

## **100% HEAVY INDUSTRIAL** CONSTRUCTION

#### **FULLY STAINLESS** STEEL Inner & Outer Drums, Front, Sides

and Top Covers

DOUBLEDECK WASHER					
Loading Capacity	(Kg/Batch)	10			
Drum Volume	(lt)	100			
Motor Power	(Kw)	1,5			
Heating Power	(Kw)	6			
Width	(mm)	825			
Depth	(mm)	885			
Height	(mm)	1.225			
Weight	(Kg)	350			

DOUBLEDECK DRYER

Loading Capacity	(Kg/Batch)	10
Drum Volume	(lt)	200
Motor Power	(Kw)	0,25
Heating Power	(Kw)	14
Width	(mm)	825
Depth	(mm)	915
Height	(mm)	955
Weight	(Kg)	140

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice







#### WASHER

Capacity	(Kg)	10
Drum Volume	(lt)	96.8
Motor	(Kw)	0,67
Electric Heating	(Kw)	4.8
Width	(mm)	680
Depth	(mm)	820
Height	(mm)	1.990
Weight	(Kg)	122

Stainless steel inner and outer drum

• Shorter washing time

• 6 recipes with electronic control

• Industrial components for longer life time

• 440 G - 1200 Rpm with dynamic balance



#### WASHER

Capacity	(Kg)	10
Drum Volume	(lt)	96.8
Max. Extraction	(G force)	440
Motor	(Kw)	0,67
Electric Heating	(Kw)	4.8

DRYER 10 Capacity (Kg) Drum Volume (lt) 198 Motor (Kw) 0,25 (Kw) 5,35 Electric Heating Width 683 (mm) Depth 704 (mm) 1.980 Height (mm) 122 Weight (Kg)

> COIN OR CARD OPERATED (Optional)



#### 10 / 10 Kg



		DRYER
Capacity	(Kg)	10
Drum Volume	(lt)	198
Motor	(Kw)	0,25
Electric Heating	(Kw)	5.35
Width	(mm)	683
Depth	(mm)	711
Height	(mm)	1.092
Weight	(Kg)	61

• High performance with exhaust ducting

• Shorter drying time with higher


resistance power

5 programmes with electronic control
Industrial components for longer life

- me
- Wide lint filter
- 180°C opening loading door









NON MARKING WITH DOUBLE MAIN BELT SYSTEM

(Optional)



GAS HEATING OPTIONAL IN ALL MODELS

PADDLE BOX & FAN SYSTEM FOR HUMIDITY COLLECTION AND DISCHARGE IN ALL MODELS


GENUINE NOMEX BELTS STAINLESS STEEL MAIN ROLL

(Optional)









#### TOLKAR ULTIMATE CONTROL SYSTEM

- 🛜 Remote access, instant mobile tracking
- USB programme transfer
- 5 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)



PLC Controlled 7" Touch Screen Panel

> (Standard in Vela 7532) (Optional)

σ

ACCORDING TO TEXTILE TYPES

### VELOCITY CONTROLLED ROLLS (Standard in Vela 7532)

(Optional)

#### AUTOMATIC TEXTILE LENGTH MEASUREMENT

IN BUILT FOLDING Vela 7532 model offers 2 - 8 primary folds between 30 - 50 cm length

> (Standard in Vela 7532) (Optional)







320 - 500 - 550 - 650 mm Roll Diameter



		Vela 3218	Vela 5520	Vela 5525	Vela 5530	Vela 5532 ᢖ
Heating Type		Electric	Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas
Cylinder Diameter	(mm)	320	550	550	550	550
Cylinder Width	(mm)	1.800	2.000	2.500	3.000	3.200
Ironing Capacity	(Kg/hour)	30-35	65-75	85-105	90-120	90-120
Working Speed	(m/min)	2-6	3,5/10,5	3,5/10,5	3,5/10,5	3/9
Motor Power	(Kw)	0,37	1,1	1,1	0,55/0,55/1,1	0,55/0,55/1,1
Fan Motor Power	(Kw)	0,37	0,37	0,37	0,37/0,37/2x0,37	0,37/0,37/2x0,37
Elec. Heating Power	(Kw)	12	22,5	27	31,5	31,5
Steam Consumption	(Kg/hour)	-	45	50	55	55
Gas Heat Power	(Kcal/hour)	-	26.350	28.900	31.570	31.570
Width	(mm)	2.385	2.589/2.823/2.966	3.089/3.323/3.466	3.589/3.823/3.966	3.930/3.930/4.090
Depth	(mm)	1.012	1.196/1.196/1.334	1.196/1.196/1.334	1.196/1.196/1.334	1.150/1.200/1.200
Height	(mm)	992	1.523/1.523/1.569	1.523/1.523/1.569	1.523/1.523/1.569	1.355/1.355/1.675
Weight	(Kg)	500	930	1.050	1.170	1.360


Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

Capacities are given for the laundry extracted at 300 G force.

It is recommended that textiles keeping more water and moisture due to thickness or knit raw material should be pre dryed in the dryers before ironing.







750 - 950 - 1200 mm **Roll Diameter** 



		Vela 7520	Vela 7525	Vela 7530	Vela 7532 🥩	Vela 9530	Vela 12030
Heating Type		Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas	Elc./Steam/Gas
Cylinder Diameter	(mm)	750	750	750	750	950	1.200
Cylinder Width	(mm)	2.000	2.500	3.000	3.200	3.000	3.000
Ironing Capacity	(Kg/hour)	80-100	90-120	120-150	100-130	160-200	200-250
Working Speed	(m/min)	4,5/13,5	4,5/13,5	4,5/13,5	3/9	6-18	7-22
Motor Power	(Kw)	1,1	1,1	1,1	1,1	2,2/2,2/2x1,5	2,2/2,2/2x1,5
Fan Motor Power	(Kw)	0,37/0,37/0,37	0,37/0,37/0,37	0,37/0,37/2x0,37	0,37/0,37/0,75	3/3/0,37+3	3/3/0,37+3
Elec. Heating Power	(Kw)	30	37,5	42	48	72	84
Steam Consumption	(Kg/hour)	65	70	75	80	100	150
Gas Heat Power	(Kcal/hour)	26.350	31.570	35.100	41.250	66.000	82.500
Width	(mm)	2.835/2.995/2.995	3.335/3.425/3.425	3.685/3.870/4.010	3.987/3.987/4.207	4.113/4.113/4.400	4.137/4.137/4.156
Depth	(mm)	1.400/1.450/1.540	1.400/1.450/1.540	1.697/1.697/1.714	1.564/1.564/1.679	2.038/2.038/2.038	2.203/2.203/2.079
Deptil				(2.260)(2.260)(2.405)		(3.016)(3.016)(3.016)	(3.181) (3.181)(3.057)
Height	(mm)	1.850/1.800/2.170	1.850/1.850/2.170	1.697/1.697/1.714	1.564/1.564/1.679	2.764/2.764/2.247	3.042/3.042/2.971
Weight	(Kg)	1.475	1.600	1.725	1.920	2.525/2.525/2.325	3.990/ 3.990/3.640

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

Capacities are given for the laundry extracted at 300 G force. It is recommended that textiles keeping more water and moisture due to thickness or knit raw material should be pre dryed in the dryers before ironing.





## VELA CHI Chest Heated Ironers











### TOLKAR ULTIMAT E CONTR OL SYSTE M

2 x 35/

Remote acces s, instant mob ile track ing

- 🚓 USB programme transfer
- 5 ready recipes, 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)



PLC Controlled 7" Touch Screen Panel ACCORDING TO TEXTILE TYPES

**CONTROLLED ROLLS** 

HIGH PRESSURE RESIST (12 BAR) GERMAN MADE CHESTS

OLKAD

#### MAXIMUM PRESSURE & PRESSING Quality via special spring crushes and pneumatic

systems







		Vela CHI 18030	Vela CHI 28030	Vela CHI 18033	Vela CHI 28033	Vela CHI 18035	Vela CHI 28035	
Heating Type		Buh/ Gaz	Buh/ Gaz	Buh/ Gaz	Buh/ Gaz	Buh/ Gaz	Buh/ Gaz	
Number of Cylinder	(Pcs.)	1	2	1	2	1	2	
Cylinder Diameter	(mm)	800	800	800	800	800	800	
Cylinder Width	(mm)	3.000	3.000	3.300	3.300	3.500	3.500	
Ironing Capacity	(Kg/hour)	150	350	160	400	180	420	
Ironing Capacity	(Pcs./hour)	250	600	275	650	300	700	
Working Speed	(m/min)	3-12	6-21	3-12	6-21	3-12	6-21	
Motor Power	(Kw)	3	2x3	3	2x3	3	2x3	
Fan Motor Power	(Kw)	0,75	1,1	7,5	1,1	7,5	1,1	
Gas Heat Power	(Kcal/hour)	66.825	123.750	66.825	123.750	66.825	123.750	
Steam Consumption	(Kg/hour)	120	220	130	240	130	240	
Width	(mm)	4.338	4.339/4.624	4.638	4.639/4.924	4.838	4.839/5.124	
Depth	(mm)	2.139	3.256/3.573	2.139	3.256/3.573	2.139	3.256/3.573	
Height	(mm)	1.545 (2.089)	1.545 (2.101)/ 1.581(1.979)	1.545 (2.089)	1.545 (2.101)/ 1.581(1.979)	1.545 (2.089)	1.545 (2.101)/ 1.581(1.979)	
Weight	(Kg)	3.700	5.800	3.750	5900	3.850	6000	

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice. It is recommended that textiles keeping more water and moisture due to thickness or knit raw material should be pre dryed in the dryers before ironing.







3000 - 3300 - 3500 mm **Roll Width** 





#### Gas Heating System

Chest and Drive System

		Vela CHI 112030	Vela CHI 212030	Vela CHI 112033	Vela CHI 212033	Vela CHI 112035	Vela CHI 212035
Heating Type		Buh/ Gaz					
Number of Cylinder	(Pcs.)	1	2	1	2	1	2
Cylinder Diameter	(mm)	1.200	1.200	1.200	1.200	1.200	1.200
Cylinder Width	(mm)	3.000	3.000	3.300	3.300	3.500	3.500
Ironing Capacity	(Kg/hour)	250	600	280	660	300	700
Ironing Capacity	(Pcs./hour)	400	1000	450	1100	500	1150
Working Speed	(m/min)	4-18	9-38	4-18	9-38	4-18	9-38
Motor Power	(Kw)	7,5	2x7,5	7,5	2x7,5	7,5	2x7,5
Fan Motor Power	(Kw)	1,5	2,2	2,2	2,2	2,2	2,2
Gas Heat Power	(Kcal/hour)	106.425	200.475	125.400	247.500	125.400	247.500
Steam Consumption	(Kg/hour)	190	360	225	440	225	440
Width	(mm)	4.835/5.075	4.839/5.059	5.135/5.375	5.139/5.359	5.335/5.575	5.339/5.559
Depth	(mm)	2.532/3.036	4.074/4.351	2.532/3.036	4.074/4.351	2.532/3.036	4.074/4.351
Height	(mm)	1.885 (2.366)/ 1.885 (2.371)	1.885 (2.225)/ 1.885 (2.225)	1.885 (2.366)/ 1.885 (2.371)	1.885 (2.225)/ 1.885 (2.225)	1.885 (2.366)/ 1.885 (2.371)	1.885 (2.225)/ 1.885 (2.225)
Weight	(Kg)	4.400	9.200	4.500	9.500	4.600	9.900


Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice It is recommended that textiles keeping more water and moisture due to thickness or knit raw material should be pre dryed in the dryers before ironing.





CAMILA MEGGY Chest Heated Ironers













Maximum Ironing Quality with Double Sided Contact In Between The Chests and Textiles

Engineered Pass System In Between Chests Without Stripes & Ribbons

Engineered Convex Type Chest System

		Camila Meggy
Heating Type		Gas
Number Of Chests	(Pcs.)	2
Chest Diameter	(mm)	2x800
Ironing Width	(mm)	3.500
Ironing Capacity	(Kg/hr)	280-320
Ironing Capacity	(Pcs/hr)	350-400
Ironing Speed	(m/min)	4-18
Motor Power	(Kw)	9,34
Fan Power	(Kw)	2 x 1,5
Gas Heating Power	(Kcal/hr)	99.000
Width	(mm)	4.383 (6.110)
Depth	(mm)	4.166
Height	(mm)	2.645
Weight	(Kg)	9.350

1 lane /	1-2-3 primary fo	ld
1-	2-3 cross fold	

2 lanes / 1-2 primary fold 1-2 cross fold

3 lanes / 1-2-3 primary fold

Minimum Maintenance With Ribbon Free & Crush Springs Free Engineered Design

Air Regulator and Automatic Air Discharge System





HUDE

**AUTOMATIC STACKER** 

**AND CONVEYOR** 

for easy handling

double stacker & conveyor

(Optional)

#### VIRGO Linen Folding

3000 - 3300 - 3500 mm Width

### TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking
- USB programme transfer
- 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

#### Single lane 2 primary 3 cross folds



Double lane 2 primary 2 cross folds and stacking (linen, f&b) (Optional)

4 lanes, 2 primary folds (f&b) (Optional)

Blanket and duvet folding (Optional)

AUTOMATIC SPEED
SYNCHRONIZATION
WITH IRONER



TELKAR

H

PLC Controlled 7" Touch Screen Panel

		VIRGO 3000	VIRGO 3300	VIRGO 3500
Folding Capacity	(Pcs/hour)	1.800	1.800	1.800
Working Speed	(m/min)	12	2-60 adjustab	le
Folding Dimensions (cm)		40	)x40 - 300x3	50
Motor Power (Total) (Kw)		3	3	3
Primary/Cross Folding		2 primary/3 cross		
Width	(mm)	3.710(5.034)	4.010(5.334)	4.210(5.534)
Depth	(mm)	1.757	1.757	1.757
Height	(mm)	3.894	3.894	3.894
Weight (Conveyor included)	(Kg)	1.750	2.050	2.200







0 0

TOLKAR



PLC Controlled 7" Touch Screen Panel

CULCURA CU

### 4 SPLIT INPUT CONVEYOR

#### Ability to fold

ABILITY TO FOLD AND SPLIT ALL TOWEL GROUPS

## AUTOMATICALLY



HEIGHT ADJUSTABLE INPUT CONVEYOR AND DOUBLE OUTPUT FLAP

## 120x200 cm

### TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking
- USB programme transfer
- 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

Folding Capacity	(Pcs/hour)	900 - 1.000
Working Speed	(m/min)	64
Folding Dimensions	(cm)	40x40 - 120x200
Motor Power (Total)	(Kw)	2
Primary/Cross Folding		2 en/2 boy
Width	(mm)	2.996
Depth	(mm)	5.200
Height	(mm)	1.408
Weight (Conveyor included)	(Kg)	1.485





# VIRGO SMARTFOLD

#### Ergonomic Stacking To Top Side Of The Machine

# 120x200 cm

Folding



PLC Controlled 7 inch Touch Screen Panel

ABILITY TO FOLD AND SPLIT ALL TOWEL GROUPS AUTOMATICALLY

3 Split Input Conveyor

#### Enhanced Flat Primary Folding System With Blades

Engineered Cross Folds Via Pistons or Air Blast Depending On The Textile Thickness Engineered Cross Fold Transportation System By Automatic Customizable Textile Thickness

0000

### TOLKAR ULTIMATE CONTROL SYSTEM

10

-

T-LKAR

- Remote access, instant mobile tracking
- USB programme transfer
- 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

Folding Capacity	(Pcs./hour)	900 - 1.000
Working Speed	(m/min)	54
Folding Dimensions	(cm)	40x40 - 120x200
Motor Power (Total)	(Kw)	2,75
Primary/Cross Folding		2 / 2
Width	(mm)	1.815
Depth	(mm)	3.565
Height	(mm)	1.775
Weight	(kg)	1.400











PLC Controlled 7" Touch Screen Panel

ABILITY TO FOLD AND SPLIT ALL TOWEL GROUPS



1 SPLIT INPUT CONVEYOR

### with ability to fold up to

## 120x240 cm

### TOLKAR ULTIMATE CONTROL SYSTEM

- Remote access, instant mobile tracking
- USB programme transfer
- 100 recipes
- (i) Reporting, amount of laundry, consumption values and working hours are being reported. (Optional)
- Smarteye centralized control and data acquisition (Optional)

Folding Capacity	(Pcs./hour)	700 - 900
Working Speed	(m/min)	30
Folding Dimensions	(cm)	40x40 - 120x240
Motor Power (Total)	(Kw)	0,61
Primary/Cross Folding		1 / 2
Width	(mm)	1.550
Depth	(mm)	3.940
Height	(mm)	1.450
Weight	(kg)	1.505






## VİRGO

Napkin, Pillow Case Stacker

- Flat stacking ability for small pieces such as napkins,
- runners, pillow cases on 4 separate lines
- Requested number of stacked textiles are collected by only
- 1 operator instead of 4
- PLC based 7" touch screen panel
- 30 meters/min working speed
- Maximum stacking dimensions
- 3000-3300-3500 width options
- 100 programmes
- Separate programming for each 4 lanes
- Reporting based on textile types and numbers
- Reporting based on programme and lanes
- Automatic speed synchronization with chest heated
- ironers and folding machines
- By pass option for large items



		VIRGO 3000	VIRGO 3300	ViRGO 3500
Working Speed	(m/min)	12-30	12-30	12-30
Capacity	(Pcs./hour)	3.600	3.600	3.600
Air Consumtion	(lt/min)	540 (6-8 bar)	540 (6-8 bar)	540 (6-8 bar)
Motor Power	(Kw)	1,5	1,5	1,5
Stacking Dimensions	(cm)	72x55	80x55	85x55
Nr. of Split Input Conveyors		4	4	4
Width	(mm)	3.480	3.780	3.980
Depth	(mm)	3.530	3.530	3.530
Height	(mm)	1.650	1.650	1.650

#### Virgo Vacuum Feader

#### vacuum Feader

#### 3000 - 3300 - 3500 mm Width

#### **Standard Features**

• Vacuum Feeders are designed for huge capacity ironers in order to perform the most demanding high quality finishing tasks. It is suitable for linens, pillow cases, table napkins and table clothes.

 Ergonomic designed structure with high efficient centrifugal fans, a forceful airflow has created to catch, to flatten, to tauten and to feed the laundry.
 All movements such as string, bending,

pulling fulfilled by operators normally, are done mechanically in order to achieve dramatically savings.

• Besides by reducing the gap of fed linens in between, efficiency of the ironer has been raised up.

• According to type of fed material, speed and vacuuming are adjustable whereas feeder relocates easily with carrier wheels.

#### AUTOMATIC SPEED SYNCHRONIZATION WITH IRONNING

Height

Weight

(mm)

(Kg)



1.273

760

Tolkar reserves changing the technical specifications of the machines due to technological necessities without prior notice

1.273

820


1.273

880





VIRGO Towel Roller





Feeding Range	(mm)	650	S
Width	(mm)	935	•
Depth	(mm)	820	•
Depth	(mm)	535	
Height	(mm)	140	

#### **Standard Features**

AUXILIARY EQUIPMENTS

- Compact and easy usage
- 200-300 pcs/hour capacity
- Bottom Shelf (Optional)



**Garment Conveyor** 



**Packing Machine** 



Mobile Hanger Trolley



Single / Double Sink Unit Stainless Steel (90-120-140-160-180-190 cm)



Mobile Working Table Stainless Steel (90-140-180-190-240-290 cm)



Laundry Trolley (270-280-500-900-1000-2000 liters)



**Stainles Steel Shelves** (90-120-140-160-180-190 cm)





# AUXILIARY EQUIPMENTS

- Tolkar Dry Cleaning Machines
- Presses
- Narrow Type Ironing Tables
- $\bullet$  Air Form Finishers
- Stain Removers
- Shirt Robots And Collar & Cuff Presses
- Trolleys
- Mobile Working Tables

- Shelves
- Sink Units
- Garment Hanger Trolleys
- Marking Machines
- Packing Machines
- Conveyor Systems
- Steam Generators
- Air Compressors
- Sewing And Overlook Machines



**Pressing Machine** Manual / Pneumatic Electric / Steam Heated





Stain Removal / Spotting Machine Electric / Steam Heated



Narrow Type Ironing Table Electric / Steam Heated




**Air From Finisher** Manual / Pneumatic Electric / Steam Heated







		CFS 300	CFS 600	CFS 900	CFS 1200	CFS 2100
Heating Type		Steam/Gas	Steam/Gas	Steam/Gas	Steam/Gas	Steam/Gas
Workwear						
%30 Humidity Retention	Pcs./Hour	150	200	300	450	700
%35 Humidity Retention	Pcs./Hour	130	150	255	385	600
%40 Humidity Retention	Pcs./Hour	110	130	220	335	525
%45 Humidity Retention	Pcs./Hour	100	150	200	300	465







# TUNNEL WASHING SYSTEMS





### DISTRIBUTORSHIPS



**Speed Queen**°









#### **COUNTRIES WE ARE EXPORTING TO**


Afganistan Albania Algeria Armenia Aruba Azerbaijan Bangladesh **Belarus Belgium** Bosna Herzigova **Bulgaria** China Colombia Croatia Denmark **Dominican Repuplic** Egypt Egypt England Estonia Ethiopia France Georgia Germany Ghana Greece Greenland Hungary India Indonesia Iran Iraq Ireland Israel Italy Jordan Kazakhstan Kenya Korea

Kosovo Kygrzystan Lebanon Libya Macedonia Madagascar Maldives **Mauritius** Mexico Morocco Netherlands Norway Oman Pakistan Phillippines Poland Portugal Qatar Romania Russia Rwanda Saudi Arabia Serbia Slovakia South Africa Spain Sri Lanka Sudan Sweden Syria Tanzania Tunisia Tunisia Turkmenistan UAE Ukraine USA Uzbekistan Vietnam

info@gvhts.com











# GATEWAY

CO

P6-71, SAIF Zone, Sharjah, United Arab Emirates Tel: +971 6 5573850 | Fax: +971 6 5573851 www.gvhts.com info@gvhts.com





